

Technical Data

TD 471 Issue 4 - Date : September 2002
Supersedes : Issue 3 - July 99
EK. Page 2/4

Packaging and Marking :

Rolls :

- 25 mm x 18.3 m : 4 rolls/case
- 51 mm x 18.3 m : 2 rolls/case
- 102 mm x 18.3 m : 1 roll/case
- 152 mm x 18.3 m : 1 roll/case
- 610 mm x 18.3 m : 1 roll/case
- 914 mm x 18.3 m : 1 roll/case

Each case is marked with product name, size, colour and manufacturer's trade name.

Colour and reference :

- Black Ref 710

Installation & Cleaning Instructions :

An installation & cleaning instruction leaflet is included in each carton.
See page 3 of this technical data sheet for surface preparation, application and maintenance instructions.

Accessories :

- 3M primers/adhesives :
 - Scotch-Grip™ FastBond 10 (for most applications).
 - Scotch-Clad™ 776 (for deeper penetration into concrete).
- 3M edge sealing compound :
 - Scotch-Seal™ 1103 Clear Sealant.

Storage conditions :

It is recommended to store the product in its closed carton, preferably at a temperature between 15°C to 30°C with humidity in the range of 50% to 60%.

Shelf life :

It is recommended to use the product within 3 years from the date printed on the carton.

Product durability :

When exposed to pedestrian traffic only, the product will stand at least 1 million crossings. (around 3 years if 1000 people walking over every day). Wheeled traffic will significantly reduce product life.

Product Disposal :

Post-consumer waste can be disposed of in appropriate containers and/or be incinerated.

European Code for waste disposal is: 20.01.04

Product Origin :

Made in USA and converted in France., in ISO 9002 certified plants.

Source of Supply :

France : S.O.A. Distribution centre

