

Technical Data

TD 470 BC – Issue 7 - Date : January 2004

Supersedes : March 2003

EK. Page 2 / 4

Chemical Resistance :

Water	R
Soap (1% Ivory Flakes in water)	R
Detergent (1% Dreft in water)	R
Bleach (5,25% sodium Hypochlorite)	I
1% Sodium Hydroxide	NR
1% Hydrochloric Acid	R
25% Sulfuric acid in water	I
Isopropyl Alcohol	R
Methyl Ethyl Ketone	I
Mineral Spirits	NR
Trichloroethylene	NR
Peanut Oil	R
Hydraulic Fluid (Skydrol 500B)	R
Motor Oil	R
Gasoline (unleaded)	IC
Diesel fuel	I
50% Anti-freeze in water	R
Wind screen washer fluid	R

R = Recommended for non continuous immersion

I = Recommended for Intermittent exposure only

NR = Not Recommended

IC = can stand incidental contact, if thorough weekly cleaning/rinsing

Note :

The recommendations noted here are based on results of 7-day immersion tests bonded to stainless steel.

Packaging and Marking :

Cleats: 50 pieces/case

Rolls :

19 mm x 18.3 m : 4 rolls/case

25 mm x 18.3 m : 4 rolls/case

51 mm x 18.3 m : 2 rolls/case

102 mm and wider : 1 roll/case

Each case is marked with product name, size, colour and manufacturer's trade name.

Installation & Cleaning

Instructions :

An installation & cleaning instruction leaflet is included in each carton.

See page 3 of this technical data sheet for surface preparation, application and maintenance instructions.

Accessories :

- 3M Primers :
 - Scotch-Grip™ EC2141
 - Scotch-Grip™ FB10
 - Scotch-Clad™ 776 (not to be used on light coloured marble and stone floors)

Primers are not recommended with the clear grade because the transparency benefit is then lost.

- 3M Edge sealing compound :
 - Scotch-Seal™ 1103 Clear Sealant

Storage conditions :

It is recommended to store the product in its closed carton, preferably at a temperature between 15°C to 30°C with humidity in the range of 50% to 60%.

Shelf life :

It is recommended to use the product within 3 years from the date printed on the carton.

Product durability :

When exposed to pedestrian traffic only, the product will stand at least 1 million crossings. (around 3 years if 1000 people walking over every day). Wheeled traffic will significantly reduce product life.

Product Disposal :

Post-consumer waste can be disposed of in appropriate containers and/or be incinerated.

European code for waste disposal is : 20.01.04

Product Origin :

Made in USA and converted in France, in ISO 9002 certified plants.

Source of Supply :

France : S.O.A. Distribution centre

