

Technical Data

TD 475. Date : July 99
Supersedes : New issue
EK. Page 1 / 4

Description :

The product consists of a fine textured resilient top surface. The reverse side is coated with an acrylic pressure sensitive adhesive covered by a removable liner. The product provides a smooth, durable, slip resistant surface for wet area applications.

Product Positioning :

Primarily for use as an anti-slip material for bare foot traffic and wet areas. The product is ideal for shower rooms, baths, changing rooms, around saunas, but also for applications on diving boards, boats, water skis...

Product Advantages :

- Non-abrasive, slip resistant surface
- Resilient construction for bare foot traffic comfort.
- Safe and hygienic
- Water resistant adhesive

Colours and references

- Clear Ref 220
- White Ref 280

Product Requirements :

Property Test method	Value	
Applied thickness ① : • MIL-D-17951 Ships	0.60 mm	
Applied weight ① : • MIL-D-17951 Ships	640 g/m ²	
Flammability : • ASTM E648-95a : (US) Average critical radiant flux (W/cm ²) : NFPA 101 : GSA Classification : • Bureau Veritas : (EU)	>1.08 Type I Class A Class 2	
Smoke density (Dm corrected) : • ASTM E622-94a : (US) 1. Flaming 2. Non-Flaming	153 170	
Minimum application temperature :	10°C 50°F	
Minimum service temperature :	minus 10°C 14 F	
Maximum service temperature :	66°C 150°F	
Dynamic coefficient of friction : • MIL-D-17951 Ships		
Surface	Condition Value	
- Rubber	Dry	1.29
	Water	0.86
	Oil	0.35
- Leather	Dry	0.66
	Water	0.79
	Oil	N/A

(Cont')

Property Test method	Value	
Static coefficient of friction :		
• MIL-D-17951 Ships		
Surface	Condition Value	
- Rubber	Dry	1.38
	Water	0.81
	Oil	0.58
- Leather	Dry	0.82
	Water	0.93
	Oil	N/A
Slip resistance :	Clear White	
• DIN 51097 (list NB) - Slip-angle - class	≥12° A ≥18° A+B	

① Typical average values

Standard Sizes :

See Standard Product Chart for available colours.

Treads :

19mm x 430mm (3/4" x 17")

Rolls :

25 mm x 18.3 m (1" x 60')
 51 mm x 18.3 m (2" x 60')
 102 mm x 18.3 m (4" x 60')
 152 mm x 18.3 m (6" x 60')
 305 mm x 18.3 m (12" x 60')
 610 mm x 18.3 m (24" x 60')

Custom sizes :

Available upon request (minimum order quantities may apply).

