

## Technical Data

**TD 474. Date : July 99**  
**Supersedes : New issue**  
**EK. Page 2/4**

### Chemical Resistance :

Water	R
Soap (1% Ivory Flakes in water)	R
Detergent (1% Dreft in water)	R
Bleach (5,25% sodium Hypochlorite)	R
1% Sodium Hydroxide	R
1% Hydrochloric Acid	R
25% Sulfuric acid in water	R
Isopropyl Alcohol	R
Methyl Ethyl Ketone	I
Mineral Spirits	NR
Trichloroethylene	NR
Peanut Oil	R
Hydraulic Fluid (Skydrol 500B)	R
Motor Oil	R
Gasoline (unleaded)	NR
Diesel fuel	NR
50% Anti-freeze in water	R
Wind screen washer fluid	R

*R = Recommended for non continuous immersion*

*I = Recommended for Intermittent exposure only*

*NR = Not Recommended*

*IC = can stand incidental contact, if thorough weekly cleaning/rinsing*

### Note :

The recommendations noted here are based on results of 7-day immersion tests bonded to stainless steel.

### Packaging and Marking :

#### Rolls :

19 mm x 18,3 m : 4 rolls/case  
25 mm x 18,3 m : 4 rolls/case  
51 mm x 18,3 m : 2 rolls/case  
102 mm x 18,3 m : 1 roll/case  
152 mm x 18,3 m : 1 roll/case  
305 mm x 18,3 m : 1 roll/case  
610 mm x 18,3 m : 1 roll/case  
914 mm x 18,3 m : 1 roll/case

Each case is marked with product name, size, colour and manufacturer's trade name.

### Installation & Cleaning Instructions :

An installation & cleaning instruction leaflet is included in each carton. See page 3 of this technical data sheet for surface preparation, application and maintenance instructions.

### Accessories :

- 3M primers :
  - Scotch-Grip™ EC2141
  - Scotch-Grip™ FB10
  - Scotch-Clad™ 776
- 3M edge sealing compound :
  - Scotch-Seal™ 1103 Clear Sealant

### Storage conditions :

It is recommended to store the product in its closed carton, preferably at a temperature between 15°C to 30°C with humidity in the range of 50% to 60%.

### Shelf life :

It is recommended to use the product within 3 years from the date printed on the carton.

### Product durability :

When exposed to bare foot traffic only, the product will stand at least 0.5 million crossings. (around 3 years if 500 people walking over every day).

Wheeled traffic will significantly reduce product life.

### Product Disposal :

Post-consumer waste can be disposed of in appropriate containers and/or be incinerated.

European code for waste disposal is : 20.01.04

### Product Origin :

Made in USA and converted in France, in ISO 9002 certified plants.

### Source of Supply :

France : S.O.A. Distribution Centre

